

# Vertex S+

## DUAL GLASS MONOCRYSTALLINE MODULE

PRODUCT: TSM-XXXNEG9R.28

PRODUCT RANGE: 420-445W

### 445W


MAXIMUM POWER OUTPUT

### 0~+5W

BINNING TOLERANCE

### 22.3%

MAXIMUM EFFICIENCY



#### Small in size, bigger on power

- Up to 445W, 22.3% module efficiency with high density interconnect technology
- Multi-busbar technology for better light trapping, lower series resistance, improved current collection and enhanced reliability
- Reduce installation cost with higher power bin and efficiency
- Boost performance in warm weather with low temperature coefficient and operating temperature



#### Dual-glass Design, more secure and sustainable

- Upgraded dual glass of Vertex S, less prone to micro-cracks and scratches on the back during installation
- Fire rating class C, weather resistance, salt spray, ammonia performance which is fully applicable in coastal, high temperature, humidity area and harsh environment



#### Ultra-low Degradation, longer warranty, higher output


- First-year degradation 1% and annual degradation at 0.4%
- Up to 25 years product warranty and 30 years power warranty



#### Universal solution for residential and C&I rooftops

- Easy for integration, designed for compatibility with existing mainstream inverters and diverse mounting systems
- Perfect size and low weight for handling and installation
- Most valuable solution on low load capacity rooftops (weight similar to backsheet version)
- Mechanical performance up to 5400 Pa positive load and 4000 Pa negative load

#### Trina Solar's Dual Glass Performance Warranty




#### Comprehensive Products and System Certificates




ISO 9001: Quality Management System  
 ISO 14001: Environmental Management System  
 ISO14064: Greenhouse Gases Emissions Verification  
 ISO45001: Occupational Health and Safety Management System




## DIMENSIONS OF PV MODULE(mm)



## I-V CURVES OF PV MODULE(435W)



## P-V CURVES OF PV MODULE(435W)



## ELECTRICAL DATA (STC) TSM-XXXNEG9R.28(XXX=420-445)

Parameter	420	425	430	435	440	445
Peak Power Watts- $P_{MAX}$ (Wp)*	420	425	430	435	440	445
Binning Tolerance- $P_{MAX}$ (W)	0 ~ +5					
Maximum Power Voltage- $V_{MPP}$ (V)	42.5	42.9	43.2	43.6	44.0	44.3
Maximum Power Current- $I_{MPP}$ (A)	9.89	9.92	9.96	9.99	10.01	10.05
Open Circuit Voltage- $V_{oc}$ (V)	50.5	50.9	51.4	51.8	52.2	52.6
Short Circuit Current- $I_{sc}$ (A)	10.53	10.56	10.59	10.64	10.67	10.71
Module Efficiency $\eta_m$ (%)	21.0	21.3	21.5	21.8	22.0	22.3

STC: Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass AM1.5. \*Measuring tolerance: ±3%.

## ELECTRICAL DATA (NOCT)

Parameter	320	324	328	332	335	339
Maximum Power- $P_{MAX}$ (Wp)	320	324	328	332	335	339
Maximum Power Voltage- $V_{MPP}$ (V)	39.7	40.0	40.4	40.7	41.0	41.3
Maximum Power Current- $I_{MPP}$ (A)	8.07	8.09	8.11	8.15	8.17	8.20
Open Circuit Voltage- $V_{oc}$ (V)	47.8	48.2	48.7	49.1	49.4	49.8
Short Circuit Current- $I_{sc}$ (A)	8.49	8.51	8.53	8.57	8.60	8.63

NOCT: Irradiance at 800W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1m/s.

## MECHANICAL DATA

Solar Cells	Monocrystalline
No. of cells	144 cells
Module Dimensions	1762×1134×30 mm (69.06×43.15×1.18 inches)
Weight	21.0kg (46.3 lb)
Front Glass	1.6 mm (0.06 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant material	EVA/POE
Back Glass	1.6mm(0.06 inches), Heat Strengthened Glass
Frame	30mm (0.06 inches) Anodized Aluminium Alloy, Black
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm <sup>2</sup> (0.006 inches <sup>2</sup> ), Portrait: 350/280 mm(13.78/11.02 inches) Length can be customized
Connector	Stabuli MC4 EVO2 / Trina Solar TS4 Plus / Trina Solar TS4

## TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of $P_{MAX}$	-0.30%/°C
Temperature Coefficient of $V_{oc}$	-0.24%/°C
Temperature Coefficient of $I_{sc}$	0.04%/°C

## MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC)
Max Series Fuse Rating	25A

## WARRANTY

25 year Product Workmanship Warranty\*\*  
 30 year Power Warranty  
 1% first year degradation  
 0.4% Annual Power Attenuation

## PACKAGING CONFIGURATION

Modules per box: 36 pieces  
 Modules per 40' container: 936 pieces

\*\*Please refer to Limited Warranty Supplement that applies to the TSM-\*\*\*NEG9R.28, TSM-\*\*\*NEG9RC.27, Products supplied after 1st Jan 2023 and installed within Australia & New Zealand rooftop market.)